



## CONTAINER SPEC' LIST

Dry Container			
Dimensions	20'GP	40'GP	40'HC
<b>Internal</b>			
Length	5,898mm	12,032mm	12,032mm
Width	2,352mm	2,352mm	2,352mm
Height	2,392mm	2,392mm	2,697mm
Door Opening Width	2,340mm	2,340mm	2,340mm
Door Opening Height	2,280mm	2,280mm	2,585mm
Cubic Capacity	33.2cu.m	67.7cu.m	76.3 cu.m
<b>External</b>			
Length	6,058mm	12,192mm	12,192mm
Width	2,438mm	2,438mm	2,438mm
Height	2,591mm	2,591mm	2,896mm
Tare Weight	2,068-2,366kg	3,557-3,876kg	3,734-4,060kg
Maximum Gross Weight	30,480kg	30,480kg	30,480kg
Maximum Payload	28,412-28,114kg	26,923-26,604kg	26,746-26,420kg



Reefer Container			
Dimensions	20'RF	40'RF	40'RHC
<b>Internal</b>			
Length	5,449mm		11,590mm
Width	2,284mm		2,294mm
Height	2,271mm		2,555mm
Door Opening Width	2,294mm		2,294mm
Door Opening Height	2,266mm		2,503mm
Cubic Capacity	28.3cu.m		67.9cu.m
<b>External</b>			
Length	6,058mm		12,192mm
Width	2,438mm		2,438mm
Height	2,591mm		2,896mm
Tare Weight	2,813-3,214kg		4,016-4,862kg
Maximum Gross Weight	30,480kg		34,000kg
Maximum Payload	27,667-27,266kg		29,984-29,138kg



Open Top Container			
Dimensions	20'OT	40'OT	
<b>Internal</b>			
Length	5,898mm	12,032mm	
Width	2,352mm	2,352mm	
Height	2,348mm	2,348mm	
Door Opening Width	2,340mm	2,340mm	
Door Opening Height	2,280mm	2,280mm	
Cubic Capacity	32.5m <sup>3</sup>	65.9m <sup>3</sup>	
<b>Roof Openings</b>			
Width Between Top Rails	2,252mm	2,232mm	
Length Between Top Troughs	5,397mm	11,531mm	
Roof Header Opening(Header Removed)			
Width Between Stubs	1,940mm	1,940mm	
<b>Cargo Lashing System</b>			
Lashing Rings Per Rail		6	12
Lashing Bars Per Post		3	3
<b>External</b>			
Length	6,058mm	12,192mm	
Width	2,438mm	2,438mm	
Height	2,591mm	2,591mm	
Tare Weight	2,134-2,421kg	3,638-3,996kg	
Maximum Gross Weight	30,480kg	30,480kg	
Maximum Payload	28,346-28,059kg	26,842-26,484kg	



Flat Rack Container			
Dimensions	20'FR	40'FR	40'FR(SUPERRACK)
<b>Internal</b>			
Length (Between end panels)	6,038mm	12,176mm	12,176mm
Length (Between corner posts)	5,638mm	11,776mm	11,615mm
Width(over bottom side rail)	2,194mm	2,230mm	2,374mm
Width (Between corner posts)	2,226mm	2,230mm	2,106mm
Height	2,233mm	1,955mm	3,478mm
			SUPER FLAT RACK



<b>External</b>			
Length	6,058mm	12,192mm	12,192mm
Width	2,438mm	2,438mm	2,438mm
Normal Height	2,591mm	2,591mm	2,591mm
Deck Height	358mm	636mm	648mm(folded)
Tare Weight	2,668-2,833kg	4,850-5,562kg	5,432-5,768kg
Maximum Gross Weight	34,000kg	45,000kg	45,000kg
Maximum Payload	31,332-31,167kg	40,150-39,438kg	39,568-39,232kg
<b>Telescopic Posts</b>			
Height can be			2,890mm
Height can be			3,200mm
Height can be			3,500mm
Height can be			3,810mm
Height can be			4,110mm

